



November 2020

 PIPE DIMENSION	DIA. 75 - 150 MM, 3" - 6"	 FOR- /BACKWARDS	55 MM - 2,2"
 SUPPLY HOSE	25 OR 50 METRES, 82 OR 164 FT	 ROTATION	360° CONTINUOUSLY
 FLEXIBLE	45° - 90° DEGREES	 GRINDS, MILLS AND CUTS	PVC, LINER, CONCRETE, IRON, CAST IRON, STAINLESS STEEL

DC SUPER FLEX

Dancutter's Extremely Flexible Cutter

DC SUPER FLEX is Dancutter's extremely flexible cutter. It can move through several 90-degree bends in a 100 mm pipe and works effortlessly whether the pipe is straight or has bends. The DC SUPER FLEX is ideal for reopening laterals or removing hard deposits like concrete from pipelines. When you are cutting, milling and grinding in pipes from 75 - 150 mm / 3" - 6"

in., DC SUPER FLEX is a powerful solution, no matter if the pipe is made of PVC, cement, concrete, cast iron or steel. The cutters are 100% Made in Denmark and, at Dancutter, we take pride in developing systems to meet the exact needs of our customers. If you have special requirements, please don't hesitate to contact us about a customized solution.



Contact Information

Dancutter a/s
 Livøvej 1
 DK-8800 Viborg

Tel: +45 9651 2150
 info@dancutter.dk

dancutter.com

Technical support

If you experience problems with the cutter or if you have any technical questions, please write to support@dancutter.dk

Order

If you need spare parts or cutting heads, please write to order@dancutter.dk



DC SUPER FLEX

Highlights

- Extremely flexible in 45° and 90° bends
- 360°-degree continuous rotation
- High-quality stainless-steel alloy
- 12" colour display
- Cuts, grinds, and mills in all materials
- User friendly
- Precise control
- Toolbox and centring tool with brushes are standard accessories
- 100% made in Denmark

Technical data

- Pipe diameter: 75 - 150 mm / 3" - 6" in.
- DC SUPER FLEX can be operated by just one person.
- The DC SUPER FLEX comes with either a 25-metre or a 50-metre hose.
- The control unit features inlet and outlet sockets for connecting a video recorder, computer, external camera, or VR headset (optional accessory).
- 12" colour display
- Spray nozzle for cleaning the camera
- Training and Service

Standard and extra accessories for DC SUPER FLEX

We offer a versatile range of accessories and spare parts for your Dancutter solutions.
Get an overview on www.dancutter.com



Specifications

 AIR SUPPLY	650 L/MIN, 22 CFM	 POWER SUPPLY	110 / 220 VAC
 AIR MOTOR	15000 RPM	 WEIGHT	25 M: 58 KG, 128 LB 50 M: 71 KG, 156.5 LB
 AIR PRESSURE	10 BAR, 145 PSI	 STAINLESS-STEEL FRAME	L: 1000 MM - W: 500 MM - H: 1030 MM